


80 lm/W 296 X 296


Features & Benefits

- *80 lm/W high lumen efficacy, with high 80+ CRI.
- TUV CB, GS, EMC and RoHS certified.
- LM80 20x35mil 2835 SMD, 97.1% lumen maintenance @ 6,000 hours.
- 3T ENTIRE PS PMMA LGP, with extrusion process; 1.2T CHIMEI PS diffuser and DXC light reflector.
- ElecCoat™ technology provides white appearance, with superb heat dissipation performance.
- NanoGap™ technology ensures the high lumen efficacy and protection of the LEDs.
- Control: DALI / 0-10V / TRIAC dim control solutions available.
- Long life: L70 @ 80,000 hours.
- 5 years warranty.

* TLP-F-6060N-40



Dimension



Model	Dimension (mm)		
	A	B	C
TLP-F-3030	296	296	11

Ordering Information

Example: TLP-F-3030N-18

Model	Size	Color Temp	Wattage
TLP-F	3030 296*296	W 3000K	18 18W
		N 4000K	
		C 6000K	

Specifications

Optical Parameters

	TLP-F-3030-18		
Size	296x296x11		
CCT	6000K	4000K	3000K
Lumen Output (lm) ±5%	1440	1440	1260
LM Efficacy (lm/W) ±5%	80	80	70
LED Type / Quantity	20x35mil chip / 48pcs		
CRI / SDCM	>80 / <6		

Electrical Parameters

Rated Power ±5%	18W
Rated / Actual Input	180-260VAC / 100~240VAC 50/60Hz
Driver Output Data	25-38VDC / 450mA / 16W
Power Factor / THD / PE	>0.9 / <20 / 88%
Driver / Connection	Removable Driver / PIP
Over Load / Short Circuit	Protection
Surge / Protection Class IEC	>1KV / Class II
Hi-pot Test Range	SELV Isolated Driver, 3750VDC / 5mA / 60s

Life



Warranty	5 years
L70 Lifetime	80,000 hours
LM80	>97.1% lumen maintance @ 6,000 hours

Others



Dim Control	DALI / 0-10V / TRIAC
Frame Color RAL	Pure white / RAL9016
IP / IK / Glow-wire	IP20 / IK06 / 650 °C
Temperature / Humidity	Working: -20 °C ~40 °C Storage: <60 °C / <75%

Photometric Data




TLP-F-3030N-18 18W 4000k



TLP-F-3030W-18 18W 3000k



Packing Information



Panel		Box		Carton	
Model No.	ABC MAX (mm)	GW (kg)	ABC MAX (mm)	GW (kg)	
TLP-F-3030	370*35*330	1.25	1020*220*380	19.65	