


Features & Benefits

- New generation IP65 LED panel, no glue, clean surface
- 100 lm/W high lumen efficacy, 80+ CRI
- TUV CB, CE and RoHS certified
- Lifud high efficiency LED driver, flicker free
- High efficiency LM80 SMD LEDs
- PS light guide panel
- ElecCoat™ technology provides white appearance, with superb heat dissipation performance
- NanoGap™ technology ensures the high lumen efficacy and protection of the LEDs
- Dimmable: DALI / 0-10V / TRIAC optional
- TpA fire-resistant PC diffuser optional
- 3 years warranty



Technical Data


Input Voltage	*220-240VAC / 50/60 Hz
PF	*≥0.95@230VAC
THD	*≤20%
Driver Efficiency	*≥90%@230VAC
Life	50,000 hrs
Dimmable Control	DALI / 0-10V / Triac Optional
Frame Color	White
IP / IK / Glow-wire	IP65 / IK06 / 650 °C
Temperature / Humidity	Working: -20-40 °C Storage: <60 °C / <75%
UGR	<22

*LF-GIF040YA LED Driver

Specifications

	TLP-6060-36-100-IP65
Rated Power (W) ±5%	36
Driver Output	33-40VDC / 800mA
CCT (K)	6000 4000 3000
LM Output (lm) ±5%	3600 3600 3240
Lm/W ±5%	100 100 90
LED Type / Quantity	J170/14C16B 224pcs
LM80 lumen maintenance	>94.7% @ 6,000hrs
CRI / SDCM	>80 / <6
Warranty	3 years

Product Dimension



Type	Dimension		
	A	B	C
TLP-6060	596	596	11



Ordering Information

Example : TLP-6060-36-NW-100-IP65




Model	Size	Wattage	Color Temp	Lm/W
TLP 6060 596*596 36 36W			WW 3000K	
			NW 4000K	100
			CW 6000K	

Photometric Data

TLP-6060-36-NW-100-IP65 36W 4000k



Packing Information



Panel		Box		Carton	
Model No.	ABC MAX (mm)	GW (kg)	ABC MAX (mm)	GW (kg)	
TLP-6060	620*35*660	4.7	630*160*680	21.2	